

MULTI 3D VN 3041

for flush aluminium and steel doors



Product features

- for flush aluminium and steel doors
- continuous 3D adjustment (side +/- 3.0 mm, height +/- 4.0 mm, compression +/- 3.0 mm)

Technical data

Property	Value
Load capacity	100.0 kg
Knuckle length	100.0 mm
Knuckle Diameter	20.0 mm
Pin diameter	10.0 mm

Notes

The load capacity mentioned above refers to the use of 2 hinges per door leaf (1 x 2 m), for detailed information please look at the chapter [technical information](#).

Also available with security pin (MSTS).

Quality marks



CE certification



IFT certification

Classification code

EN 1935 / EAD

4	7	5	1 ^{*1}	1	— ^{*2}	1	12
---	---	---	-----------------	---	-----------------	---	----

^{*1} Test evidence for functional doors to be achieved with full door sets and assemblies.


^{*2} depending on the finish

VARIANT VN - MULTI 3D VN 3041**Installation tools**


Drilling jig VARIANT MULTI
3D VN 3041

Item versions


Finish	Satin Stainless Steel (SW 040)
VPE	pack of 2
DIN	DIN right and left hand
ITEM NO.	5 030805 0 04002
ITEM NO. (SAP)	5000000440
EAN	4015471015053



front view



steel door



aluminium door