

V 0037 WF FD

door part for rebated doors with acoustic seal



Technical data

Property	Value
Load capacity	80.0 kg
Knuckle Diameter	15.0 mm
Pin diameter	8.0 mm
Cutter diameter	20.0 mm
Collar ring diameter	30.0 mm
Material thickness	2.5 mm
Screws	4.5 x 50.0 mm

Notes

The load capacity mentioned above refers to the use of 2 hinges per door leaf (1 x 2 m), for detailed information please look at the chapter [technical information](#).

Load capacity applies only to the listed frame parts.

Also available with security pin (MSTS).

The suitability for fire doors depends on the door construction.

Quality marks



CE certification



IFT certification

Classification code

EN 1935 / EAD

3	7	4	1 ^{*1}	1	— ^{*2}	0	11
---	---	---	-----------------	---	-----------------	---	----

^{*1} Test evidence for functional doors to be achieved with full door sets and assemblies.

^{*2} depending on the finish

VARIANT V - V 0037 WF FD**Installation tools**

Universal milling frame

Template 5 250587 5

Combinations

V 4200 WF
 V 4400 WF
 V 4400 WF 3 NUV
 V 4400 WF 4 NOV
 V 4400 WF 4 NUV
 V 4700 WF
 V 7900 WF VX-1
 V 8000 WF ASR
 V 8000 WF
 V 8000 WF 4 NOV/NUV
 V 8000/18 WF
 V 8000/30 WF
 V 8000 WF U
 V 8000 WF GA

Function range

fire resistance



soundproof

Item versions

Finish	Nickelled (SW 015)
VPE	pack of 20
DIN	DIN right and left hand
ITEM NO.	5 010122 0 01507
ITEM NO. (SAP)	5000000087
EAN	4015471035990

